

## ◆ PRODUCT INTRODUCTION:

This work life jacket fabric select high-strength polyester oxford, buoyancy material is EPE closed-cell foam. Usually it is designed as vest-style, tighten with 2 belts connected to the body and fasten them with buckles. It is equipped with marine grade whistle.

## ◆ PRODUCT PERFORMANCE PARAMETERS:

There were no signs of damage after ten cycles at -30°C and +65°C ambient temperature, such as shrinkage, cracking, swelling, decomposition or changes in mechanical properties.

The strength of the jacket itself and the lifting ring should be  $\geq 1764\text{N}$

Shoulder strength  $\geq 882\text{N}$

Whistle string strength  $\geq 225\text{N}$

Buoyancy: after 24 h buoyancy will loss less than 5%

Model No.: RSGY-1

Material Fabric: Polyester Oxford Textile

Inside: EPE foam

Weight: <0.5kg

Buoyancy: >75N

Reflective area:  $\geq 200\text{cm}^2$

Size: 570\*500\*80mm

Accessories: Wistle



Front



Back

Model	Buoyancy	Reflective area	Weight	Dimension	Design
RSGY-1	≥75N	≥20cm <sup>2</sup>	≤0.5kg	570*500*80mm	Vest-style

◆ **PRODUCT TECHNICAL STANDARD:**

GB/T32227/2015 《Marine Work Lifejackets》

◆ **USE OPERATION:**

- (1) Put on the life jacket like a vest.
- (2) Arrange the life jacket, fasten the upper and lower buckles and tighten them.
- (3) Check the whistle position.
- (4) Avoid contact or friction with sharp objects during use to prevent the life jacket from being worn.

◆ **VALIDITY:** If the life jacket is damaged, please replace it promptly.

**PACKAGE:** 20pcs/Carton, Volume: 0.31m<sup>3</sup>/Carton

CERTIFICATE: CCS/ZY

